

DEWALT/ POWERS TRAK-IT C5

(1) LOADING & OPERATION

1. After removing cardboard top from fuel cell insert into fuel cell compartment.
2. Insert pins into rear of magazine - Short track 20 max (2 strips of 10) / Long Track 40 max (4 strips of 10), and pull the Follower Holder over the pins to the rear of the machine and release gently. *NB Do **not** let go of the Follower so it 'pings' hard against the pins.* Also note. It will not fire the last 2 pins but another 20 (short track) or 40 (long track) can be inserted.
3. Insert the battery.
4. Insert 36mm DYNAMIFIX Washer into nosepiece.



DEWALT/ POWERS TRAK-IT C5

(2) LOADING & OPERATION

- No licence required.
- Ensure all safety precautions have been taken.
- If possible rest 'heel' on surface.
- Ensure angle of operation does not exceed 15°.
- Depress contact fully against work piece and pull trigger. **NB When new gas is inserted it may be necessary to depress the contact 3x before it will operate.**
- Release & repeat up to 3 times per second.
- Each battery will allow 5,700 cycles.
- Charging time is 2.5 hours (if battery is new or if not used for one month it is recommended that the battery is charged for 24 hours).
- Allow battery to fully discharge before recharging to avoid memory effect.
- If the battery is left in the tool for 24 hours the tool will go into sleep mode and will not operate. Remove battery and reinsert.
- The red/yellow knob adjusts the penetration depth of the nail. Leave this turned clockwise for maximum penetration.

For service and repair please contact
 Plastic Fixings Solutions Ltd
 e: dave@plasticfixings.co.uk
 m: +44 (0) 7900905102

Plastic Fixings Solutions Ltd
 Highfield House
 Congleton Road
 Scholar Green
 Stoke on Trent
 ST7 3SY
 t: +44 01782 706050
 m: +44 (0) 7900905102

PLASTIC FIXINGS
 SOLUTIONS
 FIXINGS FOR GENERAL AND BESPOKE APPLICATIONS

DEWALT/ POWERS TRAK-IT C5

(3) HEALTH AND SAFETY

Although no licence is necessary to operate this tool it is, however, recommended that you follow the following safety guidelines.

1. Always wear suitable eye and ear protection.
2. Never carry tool with finger on trigger. Do not point the tool.
3. Remove the battery when not in use or working on the tool. Last in first out!

Battery - Battery Charger

- Store indoors at temperatures below 50°
- Recharge at room temperatures between 5° and 50°.
- Do not open battery or attempt to burn.
- Observe local regulations for disposal.
- Each full charge will allow 5,700 cycles of the tool.
- A full charge will take 2.5 hours.
- Ensure terminals are clean.

Fuel cell

The fuel cell is an aerosol product, the contents are flammable. The container is under pressure.

- Each C5 fuel cell will fasten 700 pins.
- 18 month shelf life from date of production.
- Store in identified area in marked boxes.
- Never inhale contents.
- Do not smoke when handling.
- Do not expose to temperatures above 50°.
- Do not spray against open flame or hot surfaces.
- Use outside or in well-ventilated areas.
- Do not burn, open or puncture after use.
- Take care to avoid freeze burns.
- Dispose of according to local regulations.

DEWALT/ POWERS TRAK-IT C5

(4) REMOVING A PIN JAM

- Remove nails and battery

(Nails are removed by the top switch on the Follower which allows the nails to slide under the Follower. They will fall to bottom of track. Hold hand under track and press small metal switch at side and the nails will fall into your hand. Avoid letting them fall on the floor.

- Remove track with red switch. (when re-inserted make sure track is fully fitted in nose top before closing switch).
- Use Pin removal tool in tool box to remove any jammed nails.

(5) RECOMMENDATIONS

- Keep the nail strips clean and do not bend the plastic.
- Wipe track clean so that the Follower does not stick and pushes the nails into the nosepiece smoothly. Silicone lubricant spray can be used to assist this. Wipe the nosepiece clean so that the washers can be fitted easily.
- In cold weather store the fuel cells in a warm place. They do work in cold conditions but they will operate better if not frozen!
- Do not oil the nosepiece as this attracts dirt.
- For concrete use longest nails (38mm-XH). For steel use shortest XH nails. NB Piles must be clean so nails can penetrate the concrete.
- Try and keep the case as clean as possible and if the catch comes off please clip back on immediately as it is difficult to obtain spares.
- If tool won't fire check battery is charged and fuel cell is not empty. Remember that you may need to depress the contact 3 x with new gas inserted.